

REV	ECN No.	DATE	REMARK
A0	NEW	2016.04.14	新版发行

NOTES:

SPECIFICATION:

1. CURRENT RATING: 3A MAX
2. VOLTAGE: 100 VAC
3. TEMPERATURE RANGE: -30 °C ~ 85 °C
4. CONTACT RESISTANCE: 40 MILLIONHM MAX
5. INSULATION RESISTANCE: 100 MEGOHMS MIN.
6. LNSERTION FORCE : 5N~20N
7. UNMATING FORCE: 8N~20N
8. DURABILITY: 10,000 CYCLES

PCB WIRING DIAGRAM

Pin	PAD
A1,B1,A12,B12,SHELL	GND
A1,B4,A9,B9	VBUS
A5	A5
B5	B5
A6	A6
A7	A7
A2	A2
A3	A3
B11	B11
B10	B10
B2	B2
B3	B3
A11	A11
A10	A10
A8	A8
B8	B8

TABLE:

Z-CF043SLB01T-A-01	6	PCB Board	FR4	Green	
	5	SHELL	STAINLESS STEEL	NI Plated	1PCS
	4	SPRING	STAINLESS STEEL	---	2PCS
	3	SHIELDING PLATE	STAINLESS STEEL	NI Plated	1PCS
	2	CONTACT	COPPER ALLOY	COPPER ALLOY T=0.20MM, G/F PLATING ON CONTACT AREA, TIN PLATING ON SOLDER TAIL, UNDERPLATING OVERALL	1SET
	1	HOUSING	HIGH TEMPERATURE PLASTIC	BLACK	1PCS
PART NUMBER	NO.	DESCRIPTION	MATERIAL	REMARKS	QTY

MATERIAL NO.:

Z-CF043XXXXXX-X-01

REVIEW TABLE FOR DETAILS

QUALITY SYMBOL	GENERAL TOLERANCES (UNLESS SPECIFIED)
$\nabla = 0$	$\pm$ ---
$\nabla = 0$	± 0.10
$\nabla = 0$	± 0.20
$\nabla = 0$	± 0.30
$\nabla = 0$	$\pm$ ---
ANGULAR	$\pm$ ---

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO ZDT TECHNOLOGY, AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

ZDT 深圳市中科兴达科技有限公司
SHENZHEN ZDT TECHNOLOGY CO., LTD

DRAWN BY
SAM

DATE
2016.12.23

CHECKED BY
JAY

DATE
2016.12.23

APPROVED BY
JACKY

DATE
2016.12.23

TITLE
USB C F TYPE母座夹板长体10.45带PCB板

DOCUMENT NO.
ZDT-CF043

SHEET NO.
1 OF 1

DIMENSION STYLE
MM ONLY

DESIGN UNITS
METRIC

SCALE
5:1

THIRD ANGLE
PROJECTION

frame size: A4

